

Remote desk stations

E-200 Series

ES-200

Dual channel desk station

Specifications

Powering: 12-32 V, nom. 24V/ 70mA;

Connections: intercom line: XLR-3M & XLR-3F for each channel;

Dimensions/weight: 2 x 19" RU (310x89x79mm)/ 1,6 Kg Net.



The *ES-200* is a dual-channel remote station provided with a built-in speaker and gooseneck microphone. This remote station will act as a dual channel communication point in those environments where hands-free operation is preferred over the use of a headset.

The unit features 2 complete intercom channels, each one including an ON/OFF microphone switch (*push-to-talk* or latching modes) with an indicative led lamp. Apart from the built-in speaker and microphone, the unit features a male 4 Pin XLR connector, so that a regular intercom headset can be plugged when more privacy is required or when the environment is too loud. Connecting the headset will automatically switch off both the gooseneck microphone and the station speaker.

Like all the rest of the elements in the wired intercom network, the *ES-200* will be remotely powered from a base station or from a *PS-200* power supply.

As for the installing options, the unit can be inserted in a rack (2RU), embedded in a wall, or used as a desk station, all of this using the included multi-purpose rack ears.

Besides the usual intercom applications, the unit offers special functions such as the "remote messages" option and the remote "Mic-On", both controlled from the master base station. This unit is also a great complement to be used along with the *EF-200* master station when a hands-free solution is required.



Key features

- Built-in loudspeaker and *gooseneck* microphone
- Automatic interruption of *gooseneck* microphone and speaker when a headset is connected
- "Latch" or "PTT" (*push-to-talk*) MIC functions
- Remote "MIC KILL" and "BUZZ KILL" functions
- Loud buzzer sound with volume control
- Microphone limiter for ear protection and fatigue-free communication.
- Feedback control using front panel controls
- Programmable functions: Remote speaker and remote microphone activation.

ES-201

Single channel wall/desk station

Specifications

Powering: 12-32 V, 60 mA.

Connections: intercom line CH-A: XLR-3M & XLR-3F; Micro USB; *Phoenix™* connectors.

Dimensions/weight: 2 x 1/2 19" RU (200x88x52mm) / 930 gr Net (aprox.).

ES-201 station has been designed in response to the demand of in-wall stations for some specific installations. This unit features a full intercom channel, a built-in speaker and a panel microphone for hands-free operation.

The station also includes a headset connector, so that a regular intercom headset can be used when necessary. When connecting the headset, both the panel microphone and the speaker will be automatically shut down.

All setup changes of the unit are made using the front panel keys.

The optional mounting kit "OR-2-203" allows easy installation of 1 or 2 "ES-201" units in a 2 RU space.

NOTE: A similar dual-channel model ("ES-202") will be added to our catalogue in a near future.



Key features

- Built-in panel microphone and speaker.
- Headset connection.
- ON/OFF/PTT microphone switch with led indicator.
- Both the microphone and *buzzer* can be remotely deactivated from a base station ("MIC KILL" & "BUZZ KILL" functions)
- Loud *Buzzer* with level adjustment and ON/OFF switch.
- Microphone limiter for ear protection and fatigue-free communication.