



FL-200

Accessory buzzer & beacon light

Specifications

Powering: 20-32 V, nom. 24V/ 100mA.
Connections: intercom line XLR-3F + XLR-3M.
Dimensions/weight: 84x88 x105 mm/ 300 gr Net.

This portable unit makes a perfect accessory for intercom systems operating in loud environments. Thanks to its high efficiency

Xenon light, the *FL-200* beacon will help the intercom operator notice the calls even in the loudest environments.

The unit is remotely powered from the base station, same way as a regular beltpack, and includes extension connectors so that it can be easily daisy chained to the intercom line. As in a regular beltpack, the "Buzzer" function is also included and can be turned on & off as required.

Key features

- Low weight metallic enclosure (aluminium).
- Selectable operation modes: Luminous warning, *Buzzer* or both functions simultaneously.
- Remote "BUZZ KILL" function (all buzzers off).
- High luminosity Xenon strobe with 360° beam
- Extended luminous warning helps notice incoming calls.

PS-200

Intercom power supply for basic systems



Specifications

Power requirements: 90-264 VAC / 50-60 Hz/ 50VA;
Power to the system: 24 VDC/1,8A;
Connections: intercom line: XLR-3M for each line/channel. XLR-5M (both lines in one single connector);
Dimensions/weight: 1 x 1/4 19" RU (42x110x150mm)/650gr Net.

This unit has been designed to power simple intercom systems. It includes connectors for two separate intercom lines in both 3 and 5 pin wiring setups.

A "LINK" switch allows joining both channels when necessary. "BUZZ KILL" function is also included (turns off all the buzzers in the system). This unit can't be used as a communication point as it does not include a headset connection.

Key features

- Stainless steel robust case.
- Dual channel power supply.
- "A+B" link and remote "BUZZ KILL" switches.
- Universal AC input range power supply.
- Optional rack mounting ears available (model *OR-1-200*, sold separately).

Application example: basic configuration



OR-1-200

Rack mounting accessory

This mounting accessory allows the installation of a *PS-200* power supply in a 1 RU space. The kit consists of a pair of rack ears, each one containing an empty slot to install ALTAIR wired intercom belt packs and/or interfaces.

Compatible devices: *PS-200*, *EM-201*, *EM-202*, *4W2-200*, *EB-200*, *5P3-202*, *EC-200* & *ER-200*.

