

Specifications

Alimentación: 12-32 V, 90 mA.
Powering: 12-32 V, 90 mA.
Connections: Cue + Interom line CH-A: XLR-3M & XLR-3F; Intercom line CH-B: XLR-3M & XLR-3F; CH-A/CH-B: *Phoenix*™ connectors; Micro USB; Embedded XLR-4M headset connector.
Dimensions/weight: 2 x ½ 19" RU (200x88x52mm) / 1 kg Net.

ES-203CL

Wall desk station with *Cue Light*

This wall/desk unit consists on a 2-channel wired intercom station plus a cue light signals receiver, all in a compact-size device.

The unit includes a panel microphone and a speaker, which are very handy when using the system as an in-wall device for remote positions such as dressing rooms. A headset connector is also included (auto headset detection system disables panel speaker and microphone when a headset is connected to the unit).

This unit is compatible with *gooseneck* microphone *MF-200* (sold separately).

The unit incorporates supports to fix to a table/wall with differents inclination angles.

By a combination of keys you could configurate the general settings: *phantom* for *electret* mics, PTT, remote volume, remote mic activation, etc. No internal configuration jumpers/switches anymore.

Rear pannel incorporates XLR and *Phoenix*™ 3,5mm connectors to adapt the unit to reduced rear space (wall mounting).

Unit incorporates a rear panel "assistant mode" switch enabling power and communication to an assistant operator connected to the CH-B intercom line. This way the assistant is in private conversation with the *ES-203* operator, non sharing main CH-A channel.

The optional mounting kit "OR-2-203" (see right) allows easy installation of 1 or 2 "EC-203CL" units in a 2 RU space (sold separately).

Key features

- **Unit setup (electret, PTT, remote volume, remote mic ON, etc.) via key combinations (no internal adjustments required).**
- **Rear panel includes XLR and 3,5mm *Phoenix* connectors to be used when space is a limitation (in-wall installation).**
- **An external jumper sets CH-B line powering from CH-A, for installations where an auxiliary line for an assistant operator is necessary.**
- **Optional mounting kit "OR-2-203" allows easy installation of one or two "ES-203CL" units in a 2 RU space.**



Application example with an intercom system:

