

WIRELESS INTERCOM SYSTEM WB-200 Series

PRELIMINARY INFORMATION

FLASH LIGHT



WBP-210 FL



SPECIFICATIONS WBP-212FL

- DUAL CHANNEL BELTPACK. MANAGEMENT APPLICATIONS
- ◆ SINGLE A, B or COMBINED A+B LISTENING.
- ◆ SINGLE A, B or COMBINED A+B TALK FUNCTION.
- ◆ "STAGE ANNOUNCE" FUNCTION. DIRECT PA MESSAGES.
- ◆

COMMON SPECIFICATIONS WBP210 & WBP212

- DIGITAL. ENCRYPTED COMMUNICATIONS.
- ◆ LICENSE FREE FREQUENCY OPERATION.
- ◆ RANGE: 300 to 75 meters.
- ◆ DUAL INTERNAL DIVERSITY ANTENNAS
- ◆ MAIN BATTERY: LI-Ion. BATTERY LIFE 15 HOURS
- ◆ SECONDARY BATTERY: 1 X AA Alkaline. LIFE: 4-6 HOURS
- ◆ BATTERY CHARGING BY ALTAIR WBPC-210 CHARGER
- ◆ HIGH INTENSITY DUAL LED FLASH LIGHT

- WBP-210 FL ONE CHANNEL BELTPACK
- WBP-212 FL DUAL CHANNEL BELTPACK

Altair introduces a new WBP-210FL and WBP-212FL rugged belt pack versions, compatible with the WB200 Wireless Intercom series. These models includes a high attract attention FLASH led LAMP for the receiving CALL. For normal operation of the belt pack, the FLASH lamp could be disabled / dimmed by menu configuration.

These new models are conceived for diverse extreme applications: live music performance, TV ENG, open air cinema takes and other outdoor applications requiring extended reliability.

New performances are incorporated to ease the use in stress conditions: Headset connector by standard size XLR-4 for a higher durability and compatibility, long life Li-Ion battery, secondary battery supply for emergency uncharged main batteries, keyboard lock to prevent inadvertent operations, bigger illuminated switch buttons, and many others.

Preset configurations, battery remaining time, coverage and another valued information is provided by a helpfull color screen. General keyboard operation is enabled by direct keystrokes in both upper and front panels.

Other general specifications are maintained over the classic WBP-200/202 belt packs with the exception of the flash light: internal dual diversity antennas, high listening level, number of belt pack per base station, coverage, etc. This new belt pack can be combined with the classic size WBP-200/202 on the same installation.

CHASSIS

Ruggedized, full 3 mm wall thickness ABS. Comfortable feel rubberised corners. Unbreakable beltclip. Enclosure Dimension :145x95x35 m/m.

SWITCHES AND CONNECTIONS

Upper panel:


- MIC on/off/ptt illuminated switch.
- Channel A/B selector, Stage Announce switches (WBP-212)
- Volume Up-Down controls (WBP-210)

Lower panel:

- Headset connector by XLR-4 and mini XLR-4.
- USB-B for battery charging and firmware updates.

Front panel

- Up-Down volume controls. Display configuration keys.
- Illuminated CALL switch
- ON/OFF illuminated switch
- LCD color screen allowing preset configurations.



EQUIPOS EUROPEOS ELECTRONICOS

Avda. Industria, 50. Tres Cantos. Madrid www.altairaudio.com