

PROFILE 1200

PROJECTORS



PROFILE 1200




FEATURES

- High definition profile-spot projector
- Double condenser optics
- 3 zoom versions, from narrow to very wide
- Lamp access at the bottom of projector
- Aluminium and steel body with cooling fins


- LP53 1200W
- 230V
50/60 Hz
- Gx 9.5
Lct. 67 mm



12°



15/28°



22/40°

- PROFILE 1000 12° 11,0
- PROFILE 1000 15/28° 13,0
- PROFILE 1000 22/40° 12,3

MODELS

PROFILE 1200 12° (Cod. TE021.12.120)
• Black colour

PROFILE 1200 15/28° (Cod. TE022.1528.120)
• Black colour

PROFILE 1200 22/40° (Cod. TE023.2240.120)
• Black colour

TECHNICAL

- Front lenses diameter 150mm
- Central slot for gobo holder or iris diaphragm
- Gel filter cut size 167x167mm
- Reverse yoke for stand mountin
- 4 shutter blades and metal filter frame included
- 1 meter cable with cable clamp

ACCESSORY

- INCLUDED
TE021FF
- TE65
- INCLUDED
TE67
- TE66
- 86 mm
B size
60 mm

PROFILE 1200

ADMISSIBLE LAMPS

- 1200W: T29 3050K 480hrs
- 1200W: CP90 3200K 200hrs

PHOTOMETRIC

PROFILE 1200

12°	DIST	5	10	12.5	15	20	25
	LUX	3500	875	560	389	219	140
Ø(m)	1.05	2.10	2.63	3.15	4.20	5.25	

15°	DIST	5	10	12.5	15	20	25
	LUX	4300	1075	688	478	269	172
Ø(m)	1.32	2.64	3.30	3.96	5.28	6.60	

28°	DIST	5	10	12.5	15	20	25
	LUX	1400	350	224	156	88	56
Ø(m)	2.49	4.98	6.23	7.47	9.96	12.4	

22°	DIST	5	10	12.5	15	20	25
	LUX	2300	575	368	256	144	92
Ø(m)	1.94	3.88	4.85	5.82	7.76	9.70	

40°	DIST	5	10	12.5	15	20	25
	LUX	912	228	146	101	57	45
Ø(m)	3.64	7.28	9.10	10.9	14.5	18.2	

PROFILE 1200 G22

PROJECTORS



PROFILE 1200




FEATURES

- High definition profile-spot projector
- Double condenser optics
- 3 zoom versions, from narrow to very wide
- Lamp access at the bottom of projector
- Aluminium and steel body with cooling fins


- LP53 1200W
- 230V
50/60 Hz
- G 22
Lct. 63.5 mm



12°



15/28°



22/40°

- PROFILE 1000 12° 11,0
- PROFILE 1000 15/28° 13,0
- PROFILE 1000 22/40° 12,3

MODELS

PROFILE 1200 G22 12°
(Cod. TE021.12.120G) • Black colour

PROFILE 1200 G22 15/28°
(Cod. TE022.1528.120G) • Black colour

PROFILE 1200 G22 22/40°
(Cod. TE023.2240.120G) • Black colour

TECHNICAL

- Front lenses diameter 150mm
- Central slot for gobo holder or iris diaphragm
- Gel filter cut size 167x167mm
- Reverse yoke for stand mountin
- 4 shutter blades and metal filter frame included
- 1 meter cable with cable clamp

ACCESSORY

- INCLUDED
TE021FF
- TE65
- INCLUDED
TE67
- TE66
- 86 mm
B size
60 mm

PROFILE 1200

ADMISSIBLE LAMPS

- 1200W: CP93 3200K 200hrs

PHOTOMETRIC

PROFILE 1200

12°	DIST	5	10	12.5	15	20	25
	LUX	3500	875	560	389	219	140
Ø(m)	1.05	2.10	2.63	3.15	4.20	5.25	

15°	DIST	5	10	12.5	15	20	25
	LUX	4300	1075	688	478	269	172
Ø(m)	1.32	2.64	3.30	3.96	5.28	6.60	

28°	DIST	5	10	12.5	15	20	25
	LUX	1400	350	224	156	88	56
Ø(m)	2.49	4.98	6.23	7.47	9.96	12.4	

22°	DIST	5	10	12.5	15	20	25
	LUX	2300	575	368	256	144	92
Ø(m)	1.94	3.88	4.85	5.82	7.76	9.70	

40°	DIST	5	10	12.5	15	20	25
	LUX	912	228	146	101	57	45
Ø(m)	3.64	7.28	9.10	10.9	14.5	18.2	