

# PROFILE 2000

PROJECTORS



PROFILE 2000




## FEATURES

- High definition profile-spot projector
- Double condenser optics
- 2 zoom versions, from narrow to very wide
- Lamp access at the bottom of projector
- Aluminium and steel body with cooling fins

- LP44 2000W
- 230V  
50/60 Hz
- Gy 16  
LoL 70 mm



9/22°



19/32°

PROFILE 2000 9/22° **Kg** 19,0

PROFILE 2000 19/32° **Kg** 18,8

## MODELS

PROFILE 2000 9/22° (Cod. TE024.922.200)  
• Black colour

PROFILE 2000 19/32° (Cod. TE025.1932.200)  
• Black colour

## TECHNICAL

- Front lenses diameter 200mm
- Central slot for gobo holder or iris diaphragm
- Gel filter cut size 205x205mm
- Reverse yoke for stand mountin
- 4 shutter blades and metal filter frame included
- 1 meter cable with cable clamp

## ACCESSORY

- INCLUDED  
TE024FF
- INCLUDED  
TE85
- TE66
- TE65
- 86 mm  
B size  
60 mm

PROFILE 2000

## ADMISSIBLE LAMPS

2000W: CP43 3200K 400hrs  
2000W: CP72 3200K 480hrs

## PHOTOMETRIC

PROFILE 2000

19°	DIST	5	10	12.5	15	20	25
	LUX	4200	1050	672	467	263	168
	Ø(m)	1.67	3.34	4.18	5.01	6.68	8.35

9°	DIST	5	10	12.5	15	20	25
	LUX	10400	2600	1664	1156	650	416
	Ø(m)	0.8	1.60	4.85	2.40	3.20	4.00

32°	DIST	5	10	12.5	15	20	25
	LUX	1960	490	314	218	123	78
	Ø(m)	2.89	5.78	7.23	8.67	11.5	14.4

22°	DIST	5	10	12.5	15	20	25
	LUX	3920	980	627	436	245	157
	Ø(m)	1.94	3.88	4.85	5.82	7.76	9.70

# REPLAY 500

PROJECTORS


REPLAY 500



## FEATURES

- Soft beam halogen projector
- Hinged front panel for easy lamp replacement
- Symmetrical or asymmetrical version
- Aluminium and steel body with cooling fins

- LP11 300W  
LP112 500W
- 230V  
50/60 Hz
- R7s  
117 mm



REPLAY 500 **Kg** 4,4

## MODELS

REPLAY 500 Symmetrical (Cod. TE90)  
• Black colour

REPLAY 500 Asymmetrical (Cod. TE91)  
• Black colour

## TECHNICAL

- Lamp holder R7s for linear lamp, 117mm
- Aluminium reflector
- Gel filter cut size 198x230mm
- Tempered glass and protection grid are included
- 1 meter cable with cable clamp

## ACCESSORY

- INCLUDED  
TE96
- TE97
- INCLUDED  
TE101

REPLAY 500

## ADMISSIBLE LAMPS

300W: K9 3000K 2000hrs  
500W: K1 3000K 2000hrs

## PHOTOMETRIC

REPLAY 500

## TEST AT 230V WITH 500W LAMP

105°	DIST	2	3	4	5	6	7
	LUX	675	300	169	108	75	55
	Ø(m)	5.21	7.82	10.4	13	15.6	18.2

MODULAR MAXIMUM OF 3 REPLAY

