CS74



The CS74 is a 2–way high quality loudspeaker with a 5" driver for the low frequencies, and 1" coaxial tweeter mounted in the centre. It is capable of producing up to 40W RMS, with a maximum of 80W.

It ensures a brilliant reproduction of all kinds of music, and is fitted with a 100V line transformer.

There are different power taps available for 6W, 3W and 1.5W at 100V.

8 OHM 100 VOLT



Technical Highlights

	Max Power	RMS Power	Max SPL	Sensitivity 1W / 1m	Power Taps – Impedance	Frequency Response ±3 dB	Dimensions (ø x D)	Weight
CS85	60 W	30 W	112 dB	94 dB	24 / 12 / 6 Watt – 8 Ω	40Hz – 20kHz	ø 275x90	2 Kg
CS85/D	60 W	30 W	112 dB	94 dB	16 Ω	40Hz – 20kHz	ø 275x90	1.9 Kg
CS75	80 W	40 W	116 dB	97 dB	24 / 12 / 6 Watt – 8 Ω	60Hz – 20kHz	ø 205x90	1.6 Kg
CS75/D	80 W	40 W	116 dB	97 dB	16 Ω	60Hz – 20kHz	ø 205x90	1.5 Kg
CS74	80 W	40 W	105 dB	97 dB	6 / 3 / 1.5 Watt – 8 Ω	60Hz – 18KHz	ø 205x90	1.5 Kg



floating restaurant De Limonadefabriek, The Netherlands runs on Audac