

# CSE55–CSW55

The CSE55/CSW55 are professional ceiling speakers with an integrated LED light signal which can be used as visible alarm signal.

They feature a 4 1/3" single cone loudspeaker which is capable of producing up to 10W RMS, with a maximum of 20W, and ensures good reproduction of speech and background music in all situations. The speaker is fitted with a 100V line transformer and there are different power taps available for 6W, 3W and 1.5W at 100V.

The integrated LED units are available in two different colors: red (CSE55) or white (CSW55), and deliver a light intensity of 24 Lumen on a supply voltage of 24 V DC.



## Technical Highlights

	Max Power	RMS Power	Max SPL	Sensitivity 1W / 1m	Power Taps	Frequency Response ±3 dB	Dimensions (Ø x D)	Weight
CSE55	20 W	10 W	109 dB	93 dB	6 / 3 / 1.5 Watt	70Hz – 14kHz	Ø 205x70	900 g
CSW55	20 W	10 W	109 dB	93 dB	6 / 3 / 1.5 Watt	70Hz – 14kHz	Ø 205x70	900 g
CS55	20 W	10 W	109 dB	93 dB	6 / 3 / 1.5 Watt	70Hz – 14kHz	Ø 205x70	780 g
CS55/D	20 W	10 W	109 dB	93 dB	16 Ω	70Hz – 14kHz	Ø 205x70	730 g