

# LX503 MK2

## Active speaker system

- 3-Way active and passive speaker
- 2 x 40 Watt RMS
- Bass and Treble equalization
- Unbalanced RCA and Mini-Jack inputs
- Magnetically Shielded Speakers
- Adjustable brackets, Easy to mount
- Heatsink for cooling
- Line level amplification



The LX503 MKII is a 3-way stereo loudspeaker system consisting of an active and passive unit to be linked with each other. It offers a flexible solution for a wide variety of applications, producing a clear and powerful sound.

The integrated amplifier is capable of delivering a power of 2 x 40 Watt and has a line level input allowing the speaker system to be directly connected to audio sources such as CD-players, DVD players, Laptops, MP3 players or many other line level audio sources.

The line input is performed in three different ways. Unbalanced audio sources can be connected to either the RCA or 3.5mm jack connectors, while balanced audio sources can be connected to the Euro-Terminal block connectors.

The magnetically shielded loudspeakers ensure a complete immunity against interference and radiation caused by external devices, reducing the hum and noise to an absolute minimum.

Both speakers come with a sturdy steel mounting bracket, allowing proper mounting and inclining.



### Technical Highlights

	RMS Power	Sensitivity 1W / 1m	Frequency Response $\pm 3$ dB	Power Supply	Dimensions (W x H x D)	Weight (Set)
LX503MKII	2 x 40 W	88 dB	80Hz – 20kHz	230V AC / 50–60 Hz	178x240x193 mm	5.4 Kg