Type	Belt drive turntable, fully automatic
Motor	DC servo-controlled
Speeds	33-1/3 RPM, 45 RPM
Turntable Platter	Aluminum
Wow and Flutter	Less than 0.25% (WTD) @ 3 kHz
Signal-to-Noise Ratio	>50 dB (DIN-B)
Output Level	Pre-amp “PHONO”: 2.5 mV nominal at 1 kHz, 5 cm/sec Pre-amp “LINE” 150 mV nominal at 1 kHz, 5 cm/sec
Phono Pre-Amp Gain	36 dB nominal, RIAA equalized
Power Supply Requirements	100 to 240V, 50/60 Hz,0.6 A Max.
Power Consumption	1.5 W
Dimensions	359.5 mm (14.15") W x 97.5 mm (3.84") H x 373.3 mm (14.70") D
Weight	2.6 kg (5.73 lbs.)
Accessories Included	Dust cover, felt mat, platter (with drive belt), 45 RPM adapter, RCA audio cable (approx. 1.2 m (3.9')), AC adapter (approx. 1.5 m (4.9'))

AC adapter: 12 V, 2 A
Replacement Stylus: ATN3600L
Communication System: Bluetooth Version 5.0
Maximum Communication Range: Line of sight - approx. 10 m (33')
Compatible Bluetooth Profile: A2DP
Support Codec: SBC, Qualcomm aptX