



10NDL64

LF Drivers - 10.0 Inches



- 500 W continuous program power capacity
- 64 mm (2.5 in) aluminium voice coil
- 50 - 3000 Hz response
- 97 dB sensitivity
- Neodymium magnet allows a very light yet powerful motor assembly
- Ventilated voice coil gap for reduced power compression



10NDL64

LF Drivers- 10.0 Inches

SPECIFICATIONS

Nominal diameter	250 mm (10.0 in)
Nominal impedance	8 Ω
Minimum impedance	7.0 Ω
Nominal power handling ¹	250 W
Continuous power handling ²	500 W
Sensitivity (1W/1m) ³	97.0 dB
Frequency range	50 - 3000 Hz
Voice coil diameter	64 mm (2.5 in)
Winding material	Aluminium
Former material	Glass Fibre
Winding depth	14 mm (0.55 in)
Magnetic gap depth	8 mm (0.31 in)
Flux density	1.25 T

MOUNTING AND SHIPPING INFO

Overall diameter	261 mm (10.3 in)
Bolt circle diameter	245 mm (9.6 in)
Baffle cutout diameter	230.0 mm (8.8 in)
Depth	113 mm (4.4 in)
Flange and gasket thickness	13 mm (0.5 in)
Air volume occupied by driver	1.5 dm ³ (0.05 ft ³)
Net weight	2.9 kg (6.4 lb)
Shipping weight	3.5 kg (7.7 lb)
Shipping box	330x330x160 mm (13x13x6.3 in)

DESIGN

Surround shape	Double Roll
Cone shape	Exponential
Magnet material	Neodymium Inside Slug
Spider	Single
Pole design	Straight Pole
Woofers cone treatment	TWP Waterproof Both Sides
Recommended enclosure	26.0 dm ³ (0.92 ft ³)
Recommended tuning	62 Hz

SERVICE KIT

RCK10NDL648

PARAMETERS

Fs	56 Hz
Re	5.7 Ω
Qes	0.29
Qms	3.4
Qts	0.26
Vas	31.0 dm ³ (1.1 ft ³)
Sd	320.0 cm ² (50.0 in ²)
η_0	1.8 %
Xmax	6.0 mm
Xvar	7.0 mm
Mms	37 g
Bl	16.2 Txm
Le	0.9 mH
EBP	193 Hz

1. 2 hours test made with continuous pink noise signal (6 dB crest factor) within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.

B&C Speakers s.p.a.

Via Poggioromo, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) - ITALY
Tel. +39 055 65721 - Fax +39 055 6572312
mail@bcspeakers.com