CREATOR Electronics

Digital Conference System

Digital Conference System

User Manual

Please read this manual carefully before using this product

Cable

Instruction:

- CR-HL 005 5M 8-pin Aviation cable
- CR-HL 010 10M 8-pin Aviation cable
- CR-HL 020 20M 8-pin Aviation cable
- CR-HL 050 50M 8-pin Aviation cable
- CR-HL 100 100M 8-pin Aviation cable



Features:

- CR-HL* is used as the expand connection between the conference host and the expand host or the conference delegate unit.
- There are 5 models for choices: 5m, 10m, 20m, 50m, 100m
- 8 pole cable, 1 male 1 female connector.
- The maximum transferring distance is 1000m.

Instruction:

- CR-HT002 2M 8-pin “T”Aviation cable
- CR-HT005 5M 8-pin “T”Aviation cable
-



Features:

- CR-HT* is used as the shunt connection between the conference delegate unit.
- There are two models for choices: 2m, 5m.
- 8 pole cable, 1 male 1 female connector.

CR-M4KL315

Features

- capacitance MIC
- High density 5 pole aviation connector
- Switch indicator
- Apply for speech indicator

CR-CT10 “T”connector



Features

- Used as the shunt connection;
- Input connector is a female 8 pole high density connector, output connectors are two male 8 pole high density connector