

CR-WiFi6202/04B

WiFi encryption conference discussion unit



WiFi encryption conference discussion chairman unit
CR-WiFi6202B



WiFi encryption conference discussion delegate unit
CR-WiFi6204B



Size(mm):
φ = 165, H=64

Product overview

The CR-WiFi6202/4B wireless conference unit adopts special design to ensure the machine is stable, durable, and can fit any meeting room. Using the built-in antenna design; each unit built in with high performance battery which can provide continuous speaking as long as 9 hour in length; 13 hours of standby time; all functions of meeting unit can be completed with the unit panel buttons; transmission uses WiFi encryption and 2.4G RF frequency hopping technology, adopting only - ID code pairing reception speak, guarantee no unauthorized interception.

Function characteristics

- The DHCP settings, each conference unit with an independent IP address.
- WiFi transmission technology, strict digital protection to ensure the privacy of the meeting, to avoid malicious eavesdropping and jamming.
- Capacitor heart type direction microphone, with two colors indication lamp ring; speaking is red, when it is lack of electricity, the green light flashing.
- With a 3.5mm stereo headphone jack and the volume control function.
- The built-in speaker, with volume control function.
- LCD display with backlight, can display the microphone on / off, ID settings and other information.
- Chairman unit is also affected by the largest number of speakers' restrictions.
- Chairman unit has priority on closing speaking units.
- Built-in rechargeable lithium battery, battery capacity to support 9 hours of continuous speaking or static standby 13 hours.
- Using special 5 core high density airline interface.
- The professional meeting microphone, nut knob type joint connecting, can freely swap.
- The built-in loudspeaker.
- Howling inhibition function, when microphone is turned on, the built-in loudspeaker automatically shut down to prevent voice reinfusion.

Specifications

| The parameter name | CR-WiFi6202/04B |
|-----------------------------------|---|
| Connected components | |
| The bottom | Used for pluggable microphone seat; |
| Earphone jack | 1 3.5mm (0.14 inches) stereo headphone jack |
| Power supply | The DC input power supply (can access after removing the battery group) |
| Electrical parameters | |
| Frequency response | 30Hz~20KHz |
| Earphone impedance | >32 Ω <1k Ω |
| The output power of loudspeaker | 2X15mW/32 Ω |
| Wireless index | |
| Standard | IEEE Draft 2.0 802.11n |
| Radio frequency range | 4.900-5.850GHz |
| Transmit power | 15dBm |
| The antenna gain | 2dBi |
| The output voltage of the battery | 7.2V |
| Battery capacity | 3200mAH |
| Continuous speaking time | 9 special ops |
| Static standby time | 13 special ops |
| The longest charging time | 3 Special Ops |
| Color | Black |

System connection diagram

