

Specification

WM-201



General		
Size	Diameter: 90mm / 3.54 inches Height: 160mm / 6.3 inches	
Weight	0.26 kgs	
Housing	High Light permeability-UV protected PC	
Lens	High Light permeability-UV protected PC	
Mounting	Traffic Corn Wall-mounted with brace	
Lighting output	Flashing	
LED pcs	3 pcs	
Operational		
Switch	Auto / Off	
Operation time	Up to 60 hours,Overcast days could work normally	
Full charge time	8 hours (sunny day)	
Environmental		
Operating temperature	-20 °C ~60°C	
Storage temperature	-40°C ~80°C	
Moisture protection	IP65	
LEDs		
LED Type	Super bright LED	
LED Lifetime	50000~70000 hours	
LED power consumption (W)*	0.06W	
*Remark: Specifications item depend on LED colors.		
Solar Panel		

Color			
	Amber	WM - 201 – A	
	Blue	WM - 201 - B	
	Green	WM - 201 – G	
	Red	WM - 201 - R	
	White	WM - 201 – W	

Solar Panel	
Туре	Crystalline panel
Efficiency	14%~16%
Power storage	
Туре	Ni-NH
Life time	2-3 years
Listing	
Certification	CE, FCC,ISO9001

Solar LED Lighting Solutions

