
ACT-30T Bodypack Transmitter

Key Features



- Lightweight, compact size with sturdy housing.
- Top features mute switch, mini-XLR connector and antenna.
- Backlit LCD displays various parameters and indicators.
- Unique battery cover design provides easy access to operational controls and protects against accidental change of settings.
- Connector for optional MJ-70 remote mute switch cable.
- Low spurious PLL-synthesized technology enhances frequency stability and reliability. One-touch ACT syncs the transmitter and receiver frequency automatically.
- Selectable impedance for microphone or guitar/line inputs.
- 4-pin mini XLR connector is compatible with all MIPRO lavalier, headworn microphones and instrument cable.
- Highly efficient power consumption circuitry ensures long operating hours from 2 AA batteries.
- Adjustable belt clip allows wearing transmitter in up or down position.



Microphones

MU-13	Single-sided Earworn Microphone (beige)
MU-23	Omni-directional Headworn Microphone (beige, fixed connector)
MU-23d	Omni-directional Headworn Microphone (beige, detachable cont)
MU-210	Uni-directional Headworn Microphone (beige, fixed connector)
MU-210d	Uni-directional Headworn Microphone (beige, detachable cont.)
MU-53L | MU-53LS	Uni-directional Lavalier Microphone (black | beige)
MU-55L | MU-55LS	Omni-directional Lavalier Microphone (black | beige)
MU-53HN | MU-53HNS	Uni-directional Headworn Microphone (black | beige)
MU-55HN | MU-55HNS	Omni-directional Headworn Microphone (black | beige)

Accessories

ASP-30	Aerobics Bodypack Pouch (Neoprene)
BC-100	Wireless Boundary Microphone
MJ-70	Remote Mute Switch
MU-40G	Instrument Cable
TC-18	Transmitter Shielding Storage Case

Technical Specifications

Housing	Rugged Plastic
Frequency Range	UHF 480~934MHz
Bandwidth	24MHz
Oscillation Mode	PLL Synthesized
Channel Set-Up	ACT Sync
LCD Display	LCD displays working band-code, group, channel, frequency, AF input gain, RF output power, mute & lock status, battery status and error codes.
RF Output Power	10mW | 50mW (switchable)
Spurious Emissions	<-55dBc
Max. Input Level	0dBV
Mute Connector	Optional MJ-70 remote mute switch
Battery	2 AA alkaline
Battery Hours	12-14 hours (pending battery quality)
Dimensions	63(W)×82(H)x22(D)mm | 2.5(W)x3.2(H)x0.9(D)"
Weight	Approx. 81g | 2.9oz (excluding batteries)
Patents & Approvals	Patented. Telecom and safety regulations approved.

MIPRO Electronics Co., Ltd
Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw

Specifications subject to change without notice. SS015/06