

# 64512 300 W 120 V

Halogen lamps, medium/high voltage, single-ended



## Areas of application

- Professional film and TV work

#### **Product features**

- Operation at mains voltage: 120 V | 230 V | 240 V

- Color temperature: 2,900 K | 3,000 K (with longer lifespan)

- Color temperature: 3,200 K (for professional film and TV work)

- Color temperature: 3,400 K (for maximum luminous efficacy)





## Product datasheet

#### Technical data


### **Electrical data**

Nominal wattage	300.00 W
Nominal voltage	120 V

#### Photometrical data

Nominal luminous flux	9800 lm	
Color temperature	3350 K	

### **Dimensions & weight**







Diameter	18.5 mm	
Length	53.0 mm	
Illuminated field	10.0*12.5 mm <sup>2</sup>	
Filament diameter	12.5 mm	

## Lifespan

## Additional product data

Base (standard designation)	GX6.35	
Product remark	With quartz pinch technology	

## **Capabilities**

Burning position	s90

### **Certificates & standards**


EEI – Energy Label	В
--------------------	---

## Product datasheet

## **Country specific categorizations**

Order reference	64512 300W 120V

#### Product datasheet



#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321098634	64512 300 W 120 V	Folding carton box 1	111 mm x 42 mm x 42 mm	0.20 dm <sup>3</sup>	21.50 g
4008321098641	64512 300 W 120 V	Shipping carton box 12	180 mm x 127 mm x 140 mm	3.20 dm <sup>3</sup>	290.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For further information on pinch technology, please refer to the following brochure: "A whole lotta shakin' goin' on!" New halogen lamps with quartz pinch technology. (122 W 100 DE 08/05)

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.