Product datasheet



HMI 1200 W/SEL UVS

HMI | Metal halide lamps, single-ended



Areas of application

- Film and television recording in daylight conditions, in the studio or outdoors
- Film and TV production (high-wattage lamps)
- Stage (lighting for dramatic effect)
- Entertainment

Product benefits

- Very high luminous efficacy of up to 100 lm/W

Product features

- Color temperature: approx. 6,000 K (Daylight)
- Dimmable
- Hot restart capability
- High color rendering index: R_a >



March 21, 2017, 12:08:06 HMI 1200 W/SEL UVS

Product datasheet

Technical data


Electrical data

Nominal wattage	1200.00 W
Lamp voltage	100 V

Photometrical data

Color temperature	6000 К
Color rendering index Ra	» 90

Dimensions & weight



Diameter	40.0 mm
Length	220.0 mm
Light center length (LCL)	107.0 mm

Lifespan

Lifespan	1000 h	
Additional product data		
Base (standard designation)	G38	
Capabilities		

Any

Burning position

Product datasheet

Safety advice

Because of their high luminance, UV radiation (does not apply to HMI UVS) and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation of standard HMI lamps is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

References / Links

Further information can be found in the following brochures, obtainable on request from OSRAM:

"Technology and applications/Metal halide lamps"

"Guidelines for control gear and igniters for metal halide lamps"

"Availability of control gear and igniters"

"Rome. 8 pm. Overcast. No problem. HMI lamps"

"High Noon" HMI 12.000 and 18.000 W/SE/GX51

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.