
Sports/Aerobic Head-worn microphone Speech

- Ergonomically optimized behind-the-neck headband
- Moisture shield
- External shock mount for high mechanical-noise rejection



C 544 L

The new C 544 head-worn microphone from AKG is rugged, extremely easy to use, and offers outstanding price/performance. Resting securely and comfortably on the head, the C 544 is the ideal microphone for any handsfree application including gymnastics instruction, presentations, or onstage performances. With its new cheek pads, the C 544 will stay in place even if you turn your head abruptly, and a capsule shock mount reduces handling noise to a minimum. A frequency response rise at 10 kHz and rolloff below 800 Hz ensure optimum audio and intelligibility even in noisy environments. The new moisture shield that prevents sweat from penetrating into the transducer and other design features provide optimum protection from moisture. A helpful drop ring at the lower end of the gooseneck avoids that water and sweat reach the capsule. 4 additional drop rings are included in this new package.







Sports/Aerobic Head-worn microphone Speech



Polar pattern	cardioid		
Frequency range	20 to 20,000 Hz		
Sensitivity	40 mV/Pa (-28 dBV)		
Max. SPL	(k=1%) 126 dB		
Equivalent noise level	22 dB-A		
Signal/noise ratio (A-weighted)	72 dB		
Impedance	200 ohms		
Recommended load impedance	>2000 ohms		
Supply voltage	1-10 V		
Powering	<2 mA		
Connector	C 544 L: 3-pin mini XLR		
Cable	1.5 m (5 ft.)		
Finish	matte black		
Dimensions	145 x 110 x 70 mm / 5.7 x 4.3 x 2.8 in.		
Net weight	C 544 L: 30 g / 1.1 oz.		
Shipping weight	C 544 L: 200 g / 7.1 oz.		

SKU	EAN	UPC	Weight	Dimensions
2793Z00060	9002761030723	885038 03072 0	200/60g	130mm ø

www.akg.com

AKG Acoustics GmbH

Lemböckgasse 21–25, 1230 Vienna /AUSTRIA, phone: + 43 1 86654 0 e-mail: sales@akg.com

AKG Acoustics, U.S.

8400 Balboa Boulevard, Northridge, CA 91329, U.S.A., phone: + 1 818 920 3212 e-mail: akgusa@harman.com

For other products and distributors worldwide visit www.akg.com Specifications subject to change without notice.

