

W-515D / W-530D Wireless Control Fog Machine

The cutting-edge wireless control system gives Antari W series a simple setting and operation interface. Additionally, the state-of-the-art heater design upgrades the W Series fog machines to a higher level in terms of good quality fog and energy efficiency. In conclusion, Antari W Series bring users to a professional scene in an easier method.

Main Features :

- 1. Intelligent Wireless Control System**
Each machine comes with a set of wireless receiver and transmitter as standard controller. The working distance of wireless control is 50 meters in open area.
- 2. Opto-electronic Fluid Sensor**
When the fluid recipient runs dry, the fluid sensor stops pumping automatically to protect pump from burning.
- 3. More Efficient New Heat Exchanger Design**
It can generate drier fog with smaller particles. This leads to a fairly low fog fluid consumption. Compare to the equivalent power consumption heat exchangers, the same quantity of fog fluid in W series can produce 20% more fog than others.
- 4. New Advanced PCB (Printed Circuit Board)**
Design The new system can control temperature precisely and rule out the influence from outside environments as much as possible to make W series fog machines be able to work stably between - 20 and + 60 degree Celsius.

W-515D Specification

- Voltage : U.S. version : 120 Volt
Europe version : 230 Volt
U.K. version : 240 Volt
Japan version : 100 Volt
- Heater : 1,500 W
- Output : 20,000 cu.ft / min
- First Heat-up Time : 10 min
- Tank Capacity : 6 liter
- Fluid Consumption Rate : 8.3 min / liter
(100% Output)
- Remote Included : W-1 Wireless Remote
- Optional Accessories : FX-5 Flightcase,
W-515-HB Hanging Bracket
- Weight : 14 Kg
- Dimensions (mm) : L 561 x W 278 x H 186
- DMX : On board
- WDMX : On board
- Liquid Used : Antari FLR / FLG Liquid

W-530D Specification

- Voltage : U.S. version : 120 Volt
Europe version : 230 Volt
U.K. version : 240 Volt
Japan version : 100 Volt
- Heater : 3,000 W
- Output : 40,000 cu.ft / min
- First Heat-up Time : 12 min
- Tank Capacity : 6 liter
- Fluid Consumption Rate : 5.3 min / liter
(100% Output)
- Remote Included : W-1 Wireless Remote
- Optional Accessories : FX-5 Flightcase,
W-515-HB Hanging Bracket
- Weight : 19 Kg
- Dimensions (mm) : L 581 x W 278 x H 186
- DMX : On board
- WDMX : On board
- Liquid Used : Antari FLR / FLG Liquid



Control Panel (LCD Screen)



Neutrik PowerCON



W-515D Effect



W-530D Effect



FLR-5 Light Fog Liquid
FLG-5 Heavy Fog Liquid

