

Make Your Event Dynamic / Z-3000II Fog Machine

Antari proposes to you the Z-3000II, the rigorous research and development resulting stability, durability, and reliability. When it comes to ultimate performance and precision control, the Z-3000II will suit virtually any applications. These fog machine provide significant advantages in a wide array of applications where volume of fog output is critical. Around 25% electricity is saved due to high efficient power control system allowing the fogger to operate at low-level temperature.

An electronic low fluid detector is also installed which automatically weakens pump power and stops pumping when running-out of fluid. They are fully controllable via Z-20 LCD control module supplied allowing the operator to set the volume control and timing precisely to the exact percentage from 1% to 100% output. DMX connection can be worked by either 3 or 5 pin connector.

These machines are Antari's proud innovation; they are dedicated to most demanding professionals. Ideal for very large venues, outdoor event, movie production or for fire training concept.

Specification

- Voltage : U.S. version : 120 Volt
Europe version : 230 Volt
U.K. version : 240 Volt
Japan version : 100 Volt
- Heater : 3,000 W
- Output : 40,000 cu.ft / min
- First Heat-up Time : 12 min
- Tank Capacity : 6 liter
- Fluid Consumption Rate : 5 min / liter (100% Output)
- Remote Included : Z-20 Control Module
- Optional Remotes : Z-30PRO Wireless Control Module
- Weight : 19.9 Kg
- Dimensions (mm) : L 735 x W 310 x H 192
- DMX : On board
- Liquid Used : Antari FLR / FLG Liquid



▪ Z-3000II Effect



▪ Z-20 Control Module



▪ Z-30PRO Wireless Control Module (Optional)



▪ FLR-5 Light Fog Liquid
▪ FLG-5 Heavy Fog Liquid

Z-3000 Series II
Ideal Fog