AVLON®
AUDIO • VIDEO • LIGHTING
AUDIO

Özellikler

General Specifications

Specifications	D-3000	D-4000	D-6000	D-8000
Stereo Mode(both channels driver)				
8 Ω / RMS 1 kHz / 1% THD	2 x 300W	2 x 400W	2 x 800W	2 x 1600W
4 Ω / RMS 1 kHz / 1% THD	2 x 450W	2 x 650W	2 x 1300W	2 x 2500W
2 Ω / RMS 1 kHz / 1% THD	2 x 750W	2 x 1000W	2 x 2000W	2 x 4000W
Bridge Mono Mode				
8 Ω / / RMS 1 kHz / 1% THD	1000W	1500W	2500W	4800W
4 Ω / RMS 1 kHz / 1% THD	3000W	4000W	6000W	8000W
MAXIMUM DISTORTION *8 ohms* *20-20kHz, 1dB below rated power*	0.2%			
FREQUENCY RESPONSE *8 ohms*	20-20kHz, +/-0.2dB, all models.			
NOISE FLOOR *20Hz-20kHz*	-95dB			
DAMPING FACTOR *8 ohms*	400	400	600	800
OUTPUT CIRCUIT TYPE	Class-D			
INPUT SENSITIVITY	1.0V, 1.5V, 2.0V			
INPUT IMPEDANCE	>10k ohms, balanced or unbalanced, all models.			
FRONT PANEL	POWER switch(Push on/Push off), Two Volume control knobs (one per ch)			
INDICATORS	LOGO, SIGNAL(2 x Green), CLIP(2 x Red), PROTECTION(2 x Red)			
OUTPUT CONNECTORS	Speakon(one per ch), 5-way binding posts			
INPUT CONNECTORS *Each channel:*	XLR-3-31 (two per ch)			
AMPLIFIER AND LOAD PROTECTION	Short circuit, open circuit, thermal, RF protection. On/off muting, DC fault shutdown, active inrush limiting.			
AC POWER, CORDSET *200-240V 50/60Hz*	T10A/250V	T12A/250V	T20A/250V	T30A/250V
DIMENSIONS *All models*	483x 328x89mm	483x 328x89mm	483x 440x89mm	483x 463x132mm
WEIGHT *Net*	12.6Kg	16Kg	24Kg	35Kg
Shipping	15Kg	18.3Kg	27.2Kg	39.5Kg

Due to continuous development these specifications are subject .to change without notice

Start
Elektronik San. ve Tic. Ltd. Şti.

Start Elektronik San ve Tic. Ltd Şti.
www.startelektronik.com.tr
www.avlonpro.com
info@ avlonpro.com

İLETİŞİM
Tel: 0312 485 60 00
Tel: 0312 446 96 66
Fax:0312 485 60 62

ADRES
Şafak Mahallesi 854.Cadde 8/A 06830
Gölbaşı / ANKARA TÜRKİYE