PVX™ Series Enclosures

RUGGED, RELIABLE, FLYABLE...BEST IN CLASS PERFORMANCE

PVX™ 12/PVX™ 15

The PVX™ two-way sound reinforcement systems are based on a heavy-duty woofer and a RX™14 titanium diaphragm dynamic compression driver mounted on a 100 by 50 degree coverage Quadratic Throat Waveguide™.

The lightweight yet rugged injection-molded plastic enclosure with molded-in stand mount cup facilitates portable use for live music or PA sound. The trapezoidal cabinet has three handles for ease of portability, and an extra 45-degree angled section on the right side to allow use as a floor monitor. Five sets of flying/mounting points, two on the top, two on the bottom, and one on the side, with a total of 16 cabinet inserts, provide for the ultimate in installation flexibility. A black powder coated perforated steel grille provides driver protection and a professional appearance.

Two-way sound reinforcement enclosure; Heavy-duty woofer with 2 3/8" voice coil & 50oz. magnet; RX14 compression driver, with 1.4" titanium diaphragm; Exclusive Quadratic Throat Waveguide™ technology, 100 by 50 degree coverage; Asymmetrical horn aims the sound down 10°, at the audience, not over their heads; Crossover network for driver protection and EQ; High frequency driver protection; Durable plastic injection-molded trapezoidal enclosure; Extra angled section on right side allows floor monitor use; Full-coverage heavy-duty perforated steel grilles, with powder coat finish; Pole mount molded-in; Top, bottom, and right side flying point inserts.

PVX 12 03602440
Dimensions (HxWxD):
F 24.5" x 16.1" x 15" / 622.3mm x 409mm x 381mm
R 22.75" x 8.75". x 15" / 578mm x 222.3mm x 381mm
Weight: 37lbs / 16.8kg

PVX 15 03602470
Dimensions (HxWxD):
F 28.25" x 18.9" x 18.71" / 717.6mm x 480mm x 475mm
R 26.25" x 10.25" x 18.71" / 667mm x 260.35mm x 475mm
Weight: 47lbs / 21.32kg

The heavy-duty woofer has a 2 3/8" voice coil diameter, and a 50oz. magnet for 200 watts of continuous chest-pounding bass. The RX™14 compression driver tweeter is coupled to a Quadratic Throat constant directivity waveguide, with smooth, even response, low distortion and good high frequency dispersion. This horn has an asymmetrical vertical polar response, aiming the main energy lobe down 10°, so it is aimed at the audience, instead of over their heads. This helps reduce ceiling reflections for greater clarity and gain before feedback.



Molded-in stand mount cup facilitates portable use for live music or PA sound. PVX 12 shown mounted on PVXp Subwoofer.

FEATURING:
Exclusive Quadratic Throat Waveguide™ Technology

Asymmetrical Quadratic Throat Waveguide horns aim their coverage patterns 15° upward and 35° downward – directing sound to your audience, not over their heads.





400W PROGRAM
800W PEAK POWER HANDLING



FEATURING:
Top, bottom, and right side flying point inserts
Five sets of flying/mounting points, two on the top, two on the bottom, and one on the side, with a total of 16 cabinet inserts, provide for the ultimate in installation flexibility.