SP® 12M



OVERVIEW

Engineered for optimal sound reproduction with proven reliability continuing a 30-year legacy, Peavey SP enclosures feature patented asymmetrical Quadratic Throat Waveguide™ technology that helps deliver pristine, precise sound; Black Widow® loudspeakers with Kevlar®-impregnated cones, 4" ribbon-wire voice coils and exclusive field-replaceable baskets; the patented Radialinear™ Planar Phase Correction System; and titanium compression drivers with ferrofluid cooling.

FEATURES

- Two-way, full-range floor monitor
- Sound Guard ™ III tweeter protection
- Frequency response: 108 Hz to 14 kHz
- -10 dB cutoff: 86 Hz
- Sensitivity: 98 dB (1W/1m)
- RX™ 22 compression driver with ferrofluid cooling and a 2 inch titanium diaphragm
- Two 1/4 inch phone jack full-range inputs in parallel with a 4 pin Neutrik(T) jack
- Impedance: 8 Ohms
- 30 or 45 degree baffle angle
- HammerHead™ durable covering material
- Perforated steel metal grille
- One 12 inch BWX Black Widow® 4 inch voice coil woofer with Kevlar®/carbon fiber cone and field-replaceable basket, flat-wound voice coil and cast frame basket
- Stand mount adapter
- Power handling: 1000 Watts program, 2000 Watts peak
- Weight Unpacked: 53.00 lb(24.04 kg)
- Weight Packed: 59.00 lb(26.76 kg)
- Width Packed: 23.5"(59.69 cm)
- Height Packed: 25.5"(64.77 cm)

- Depth Packed: 15.937"(40.47998 cm)