SP® 15M



OVERVIEW

Engineered for optimal sound reproduction with proven reliability continuing a 30-year legacy, Peavey SP enclosures feature patented asymmetrical Quadratic Throat Waveguide™ technology that helps deliver pristine, precise sound; Black Widow® loudspeakers with Kevlar®-impregnated cones, 4" ribbon-wire voice coils and exclusive field-replaceable baskets; the patented Radialinear™ Planar Phase Correction System; and titanium compression drivers with ferrofluid cooling.

FEATURES

- Power handling: 1000 Watts program, 2000 Watts peak
- 8 Ohms
- -10 dB cutoff: 66 Hz
- Sensitivity: 99 dB (1W/1m)
- Sound Guard™ HF driver protection circuit
- Frequency response: 90 Hz - 14 kHz
- Neutrik® full-range jack
- 30 or 45 degree baffle angle
- Baltic birch enclosure
- New grille
- RX™ 22 compression driver with ferrofluid cooling and a 2 inch titanium diaphragm
- 45 degree baffle orientation
- One 15 inch BWX Black Widow® woofer with Kevlar®/carbon fiber cone and field-replaceable basket, flat-wound voice coil and cast-frame basket
- HammerHead™ durable covering material
- Two-way, full-range floor monitor
- Weight Unpacked: 56.99 lb(25.85 kg)
- Weight Packed: 62.99 lb(28.57 kg)
- Width Packed: 24.75"(62.865 cm)

- Height Packed: 28"(71.12 cm)
- Depth Packed: 16.25"(41.275 cm)