SP 4BX



OVERVIEW

Engineered for optimal sound reproduction with proven reliability continuing a 30-year legacy, Peavey SP enclosures feature patented asymmetrical Quadratic Throat Waveguide™ technology that helps deliver pristine, precise sound; Black Widow® loudspeakers with Kevlar®-impregnated cones, 4" ribbon-wire voice coils and exclusive field-replaceable baskets; the patented Radialinear™ Planar Phase Correction System; and titanium compression drivers with ferrofluid cooling.

FEATURES

- Quasi-three-way, full-range, bi-ampable sound reinforcement system
- 2000 watts program, 4000 watts peak
- Patented Asymmetrical Quadratic Throat Waveguide™ technology
- Patented Radialinear Planar Phase Correction System
- Sound Guard™ III tweeter protection
- Two 15 inch BWX Black Widow® 4 inch voice coil woofers
- Sensitivity: 100 dB (1W/1m) anechoic
- Full-range inputs include a Neutrik® Speakon® 4 pin jack and two 1/4 inch phone jacks
- Bi-amp capability via internal wiring jumper
- Trapezoidal enclosure
- HammerHead® durable covering material
- RX™ 22 compression driver with ferrofluid cooling
- Frequency Response: 52 Hz to 17 kHz (+/- 3 dB)
- Pocket Casters
- Weight Packed: 133.49 lb(60.55 kg)
- Width Packed: 25.75"(65.405 cm)
- Height Packed: 52.37"(133.0198 cm)
- Depth Packed: 23"(58.42 cm)