Versarray™ 112



OVERVIEW

The Versarray 112 ribbon-driver line array utilizes a high-performance, lightweight 12" Neo Black Widow® woofer featuring a dual 4" flat wound voice coil with a neodymium magnet structure in a 13-ply Baltic birch enclosure. The Versarray 112 offers extreme versatility and performance in modular coverage of small- to medium-sized venues and is intended for use with Versarray 118 or 218 subs. Sound Guard™, Peavey's proprietary protection circuitry, provides long- and medium-term driver overload protection without impairing musical transients or dynamics. Available in Black or Off-white

FEATURES

- Low-Frequency Power Handling: 1000 watts program, 2000 watts peak
- Frequency Response: 100 HZ to 24 kHz
- 90° H x 15° V coverage pattern (per line array module)
- Single 12" vented Black Widow® Neo woofer with 4" voice coil
- 320 watts peak
- HF-16/4 ohms selectable, LF-8 ohms
- Two 4.75" ribbon drivers on Waveguide
- Two Neutrik® four-pin Speakon® inputs
- Sound Guard™ tweeter protection
- Dual stand-mount cups: one perpendicular and one 5 degrees angled down
- High-Frequency Power Handling: 160 watts program
- Durable GatorHyde® finish
- Weight Unpacked: 55.12 lb(25 kg)
- Weight Packed: 60.85 lb(27.6 kg)
- Width Packed: 17"(43.18 cm)
- Height Packed: 27.25"(69.215 cm)
- Depth Packed: 14.5"(36.83 cm)