

NON-POWERED ENCLOSURES

Versarray™ Series Enclosures

INNOVATIONS FOR THE MOST CHALLENGING LIVE MUSIC PRODUCTIONS

The Peavey Versarray™ features planar ribbon drivers, neodymium-loaded woofers and exclusive angle adjustment technology to set a new benchmark for high fidelity, high-level sound reinforcement.

A veteran of major concert tours such as Ozzfest, Tim McGraw and the Rockstar® Mayhem Festival, the Versarray line array offers extreme versatility in the most demanding sound-reinforcement applications.

The Versarray system's exclusive bracket-and-pin flying hardware allows maximum articulation from each enclosure. This highly flexible rigging system gives users a multitude of array possibilities, from traditional flying to ground stacking or pole mounting. Versarray accessory packages include everything you need to achieve perfect sound, from locking pins and "fly bars" to a crankable speaker lift.



VERSARRAY™ 112 MK II

The Versarray 112 MK II ribbon-driver line array utilizes a high-performance, 12" Black Widow® woofer featuring a dual 4" flat wound voice coil with a neodymium magnet structure in a 13-ply Baltic birch enclosure. The Versarray 112 MK II offers extreme versatility and performance in modular coverage of small-to medium-sized venues and is intended for use with Versarray 118 or 218 subs. SoundGuard™, Peavey's proprietary protection circuitry, provides long-and medium-term driver overload protection without impairing musical transients or dynamics. The low-frequency section handles 1,000 watts program (2,000W peak), while the high-frequency sections handles 160 watts program, (320W peak).

Dimensions (HxWxD):
14.06" x 25.25" x 11.75" / 357.1mm x 641.35mm x 298.5mm
Weight: 56lbs / 25.4kg
03008650



VERSARRAY™ 212 MK II

The Versarray™ 212 MK II array is loaded with dual 12" Black Widow® Neo speakers with 4" dual voice coils, ten 2.5" neo midrange speakers arranged in two banks of five each, and four 4.75" planar dynamic ribbon tweeter line sources on a waveguide. Designed to provide modular coverage of medium to large venues and intended for use with the companion Versarray sub models, the Versarray 212 MK II offers extreme versatility in highly demanding performance situations. The low-frequency section handles 2,000 watts program (4,000W peak), while the mid and high sections handle 400 watts program (800W peak) each.

Dimensions (HxWxD):
14.06" x 43.13" x 11.75" / 357.1mm x 1095.5mm x 298.5mm
Weight: 102lbs / 46.3kg
00584470