SB-6310

VGA • AUDIO CAT5 EXTENDERS

VGA AUDIO CAT5

4x WAY CAT5 Transmitter • 2x WAY CAT5 REPEATER-RECEIVER

SB-6310 4x(Tx) TRANSMITTER Distribution Amplifier

Inputs :
1x VGA-Audio

Outputs :
1x VGA-Audio Preview Output
4x Tx Transmitters Outputs

SB-6310R 2xVGA RECEIVER+REPEATER(Auto Type)

Inputs :
1x Rx Receiver

Outputs :
2x VGA-Audio
1x Repeater (Loop Output)





03

FEATURES

1. Support VGA-RGBHV & Stereo Audio(AR/AL) CAT-5 Transmitter and Repeater + Receiver Extender
2. SB-6310: Input : 1x VGA+Audio
   Output : 1x VGA-Audio Preview, 4x Tx Transmitter
3. SB-6310R: Input : 1x CAT5(RX) Receiver
   Output : 2x VGA+Audio Distribution Amplifier
   1x CAT5(TX) Extend Loop Output
4. Support PC Resolution: VGA(640x480) / SVGA(800x600) / XGA(1024x768) SXGA(1280x1024) / UXGA(1600x1200).
5. Support HDTV Resolution: 480p / 720p / 1080i /1080p
6. Support one Loop Output port.
7. Support adjustment of RGB signals TINT and BRIGHTNESS
8. Extension distance is up to 100m(330ft)
9. Enclosure: wall mount ear includes

SPECIFICATIONS

1. Type of CAT5 :	Transmitter(TX) / Repeater + Receiver(RX)
2. Type of Signal:	VGA(RGBHV) & Stereo Audio (AR/AL) connectors
3. Video Bandwidth :	Large Signal Bandwidth: 225Mhz, -3dB
	Small Signal Bandwidth: 450Mhz, -3dB
4. Output Balance Error :	-60dB @50Mhz
5. High Isolation between Amplifier	80dB@10Mhz
6. Audio- In Impedance :	10 Ohms
7. Audio Frequency Response :	20HZ to 20KHz, +/-1db
8. Safety Approvals :	CE, FCC,VCCI
9. Dimension:	4.45" x 2.87" x 1.15"(112.9mm x 73mm x 29.1mm)
10. Power Supply :	DC 12V /1A Max
	Use Universal Switch Type 50/60Hz, 100~240VAC
11. Net Weight (Unit Only) :	About 0.2kg/0.44 lb

INSTALLING DIAGRAM

