RECORDING

Capture your sound—in the studio or on the road.

PG27

Multi-Purpose

Side-Address Cardioid Condenser Microphone



Equipped with a large-diaphragm capsule, the PG27 maintains a flat frequency response for natural reproduction of instruments and vocals.



20Hz – 20kHz

PG27USB

Multi-Purpose

Side-Address Cardioid Condenser Microphone



USB Plug and Play.

The PG27USB is designed to deliver the natural audio reproduction of the PG27, enhanced with digital output, control and flexibility. Simply connect to a computer for convenient digital recording.



20Hz – 20kHz

PG42

Vocal

Side-Address Cardioid Condenser Microphone



Specially tuned for detailed reproduction of lead vocals and instrument applications, the PG42 includes a switchable -15dB pad and high pass filter for increased flexibility.



20Hz – 20kHz

PG42USB

Vocal

Side-Address Cardioid Condenser Microphone



USB Plug and Play.

The PG42USB is designed to deliver the lead vocal and instrument reproduction of the PG42, enhanced with digital output, control and flexibility. Simply connect to a computer for convenient digital recording.



20Hz – 20kHz


Key: | **Operating Principle** Dynamic, Condenser | **Polar Pattern** OmniDirectional, Cardioid, SuperCardioid | **Frequency Response** Flat, Tailored


Technical Specifications



PG27
PG27USB

Multi-Purpose





PG27:

Frequency Response:	20 Hz – 20 kHz
Output Level (at 1,000 Hz):	-41 dBV/Pa, 1 Pascal=94 dB SPL
Net Weight:	438 grams (15.45 ounces)

PG27USB:

Frequency Response:	20 Hz – 20 kHz
Output Level (at 1,000 Hz):	-33 dBFS/Pa (at minimum gain)
Net Weight:	452 grams (15.94 ounces)


USB Digital Recording Features:


- Zero-Latency Monitoring
- Integrated Pre-Amp with Microphone Gain Control
- Headphone Jack
- Monitor Mix Control for blending microphone and playback audio
- 16 bit, up to 48 kHz sample rate for better-than-CD-quality audio



PG42
PG42USB

Vocal





PG42:

Frequency Response:	20 Hz – 20 kHz
Output Level (at 1,000 Hz):	-35 dBV/Pa, 1 Pascal=94 dB SPL
Net Weight:	439 grams (15.49 ounces)

PG42USB:

Frequency Response:	20 Hz – 20 kHz
Output Level (at 1,000 Hz):	-29 dBFS/Pa (at minimum gain)
Net Weight:	453 grams (15.98 ounces)


USB Digital Recording Features:


- Zero-Latency Monitoring
- Integrated Pre-Amp with Microphone Gain Control
- Headphone Jack
- Monitor Mix Control for blending microphone and playback audio
- 16 bit, up to 48 kHz sample rate for better-than-CD-quality audio



PG48

Vocal







Frequency Response:	70 Hz – 15 kHz
Output Level (at 1,000 Hz):	-52 dBV/Pa, (2.5 mV), 1 Pascal=94 dB SPL
Net Weight:	314 grams (11.1 ounces)



PG58

Vocal







Frequency Response:	60 Hz – 15 kHz
Output Level (at 1,000 Hz):	-53 dBV/Pa, (2.2 mV), 1 Pascal=94 dB SPL
Net Weight:	321 grams (11.3 ounces)



PG57

Instrument







Frequency Response:	50 Hz – 15 kHz
Output Level (at 1,000 Hz):	-56 dBV/Pa, (1.6 mV), 1 Pascal=94 dB SPL
Net Weight:	324 grams (11.5 ounces)

PG81

Instrument







Frequency Response:	40 Hz – 18 kHz
Output Level (at 1,000 Hz):	-48 dBV/Pa, (4.0 mV), 1 Pascal=94 dB SPL
Net Weight:	250 grams (8.8 ounces) less battery



PG52

Drum







Frequency Response:	30 Hz – 13 kHz
Output Level (at 1,000 Hz):	-54 dBV/Pa, (2.0 mV), 1 Pascal=94 dB SPL
Net Weight:	470 grams (16.8 ounces)



PG56

Drum





Frequency Response:	50 Hz – 15 kHz
Output Level (at 1,000 Hz):	-56 dBV/Pa, (1.6 mV), 1 Pascal=94 dB SPL
Net Weight:	323 grams (11.4 ounces)

SHURE®
LEGENDARY PERFORMANCE™

United States:
Shure Incorporated
5800 West Touhy Avenue
Niles, IL 60714-4608 USA

Phone: 847-600-2000
Fax: 847-600-6404
Email: info@shure.com

Europe, Middle East, Africa:
Shure Europe GmbH
Wannenäckerstr. 28,
74078 Heilbronn, Germany

Phone: 49-7131-72140
Fax: 49-7131-721414
Email: info@shure.de

Asia, Pacific:
Shure Asia Limited
3/F, Citicorp Centre
18 Whitfield Road
Causeway Bay, Hong Kong

Phone: 852-2893-4290
Fax: 852-2893-4055
Email: info@shure.com.hk

Canada, Latin America, Caribbean:
Shure Incorporated
5800 West Touhy Avenue
Niles, IL 60714-4608 USA

Phone: 847-600-2000
Fax: 847-600-6446
Email: international@shure.com

©2009 Shure Incorporated

AL1592 10K 01/09