

RECORDING

Capture your sound—in the studio or on the road.


PG27

Multi-Purpose

Side-Address Cardioid
Condenser Microphone



Equipped with a large-diaphragm capsule, the PG27 maintains a flat frequency response for natural reproduction of instruments and vocals.



20Hz – 20kHz

PG27^{USB}


Multi-Purpose

Side-Address Cardioid
Condenser Microphone



USB Plug and Play.

The PG27^{USB} is designed to deliver the natural audio reproduction of the PG27, enhanced with digital output, control and flexibility. Simply connect to a computer for convenient digital recording.



20Hz – 20kHz


PG42

Vocal

Side-Address Cardioid
Condenser Microphone



Specially tuned for detailed reproduction of lead vocals and instrument applications, the PG42 includes a switchable -15dB pad and high pass filter for increased flexibility.



20Hz – 20kHz

PG42^{USB}


Vocal

Side-Address Cardioid
Condenser Microphone



USB Plug and Play.

The PG42^{USB} is designed to deliver the lead vocal and instrument reproduction of the PG42, enhanced with digital output, control and flexibility. Simply connect to a computer for convenient digital recording.



20Hz – 20kHz

Technical Specifications




PG27 PG27USB

Multi-Purpose



Measured at 1000 Hz



PG27:

Frequency Response: 20 Hz – 20 kHz
Output Level (at 1,000 Hz): -41 dBV/Pa,
 1 Pascal=94 dB SPL
Net Weight: 438 grams (15.45 ounces)

PG27USB:

Frequency Response: 20 Hz – 20 kHz
Output Level (at 1,000 Hz): -33 dBFS/Pa
 (at minimum gain)
Net Weight: 452 grams (15.94 ounces)

USB Digital Recording Features:

- Zero-Latency Monitoring
- Integrated Pre-Amp with Microphone Gain Control
- Headphone Jack
- Monitor Mix Control for blending microphone and playback audio
- 16 bit, up to 48 kHz sample rate for better-than-CD-quality audio




PG42 PG42USB

Vocal



Measured at 1000 Hz



PG42:

Frequency Response: 20 Hz – 20 kHz
Output Level (at 1,000 Hz): -35 dBV/Pa,
 1 Pascal=94 dB SPL
Net Weight: 439 grams (15.49 ounces)

PG42USB:

Frequency Response: 20 Hz – 20 kHz
Output Level (at 1,000 Hz): -29 dBFS/Pa
 (at minimum gain)
Net Weight: 453 grams (15.98 ounces)

USB Digital Recording Features:

- Zero-Latency Monitoring
- Integrated Pre-Amp with Microphone Gain Control
- Headphone Jack
- Monitor Mix Control for blending microphone and playback audio
- 16 bit, up to 48 kHz sample rate for better-than-CD-quality audio




PG48

Vocal



Measured at 1000 Hz



Frequency Response: 70 Hz – 15 kHz
Output Level (at 1,000 Hz): -52 dBV/Pa, (2.5 mV),
 1 Pascal=94 dB SPL
Net Weight: 314 grams (11.1 ounces)




PG58

Vocal



Measured at 1000 Hz



Frequency Response: 60 Hz – 15 kHz
Output Level (at 1,000 Hz): -53 dBV/Pa, (2.2 mV),
 1 Pascal=94 dB SPL
Net Weight: 321 grams (11.3 ounces)




PG57

Instrument



Measured at 1000 Hz



Frequency Response: 50 Hz – 15 kHz
Output Level (at 1,000 Hz): -56 dBV/Pa, (1.6 mV),
 1 Pascal=94 dB SPL
Net Weight: 324 grams (11.5 ounces)




PG81

Instrument



Measured at 1000 Hz



Frequency Response: 40 Hz – 18 kHz
Output Level (at 1,000 Hz): -48 dBV/Pa, (4.0 mV),
 1 Pascal=94 dB SPL
Net Weight: 250 grams (8.8 ounces)
 less battery




PG52

Drum



Measured at 1000 Hz



Frequency Response: 30 Hz – 13 kHz
Output Level (at 1,000 Hz): -54 dBV/Pa, (2.0 mV),
 1 Pascal=94 dB SPL
Net Weight: 470 grams (16.8 ounces)




PG56

Drum



Measured at 1000 Hz



Frequency Response: 50 Hz – 15 kHz
Output Level (at 1,000 Hz): -56 dBV/Pa, (1.6 mV),
 1 Pascal=94 dB SPL
Net Weight: 323 grams (11.4 ounces)

SHURE®

LEGENDARY
PERFORMANCE™

United States:
 Shure Incorporated
 5800 West Touhy Avenue
 Niles, IL 60714-4608 USA

Phone: 847-600-2000
 Fax: 847-600-6404
 Email: info@shure.com

Europe, Middle East, Africa:
 Shure Europe GmbH
 Wannenaekerstr. 28,
 74078 Heilbronn, Germany

Phone: 49-7131-72140
 Fax: 49-7131-721414
 Email: info@shure.de

Asia, Pacific:
 Shure Asia Limited
 3/F, Citicorp Centre
 18 Whitfield Road
 Causeway Bay, Hong Kong

Phone: 852-2893-4290
 Fax: 852-2893-4055
 Email: info@shure.com.hk

**Canada, Latin America,
 Caribbean:**
 Shure Incorporated
 5800 West Touhy Avenue
 Niles, IL 60714-4608 USA

Phone: 847-600-2000
 Fax: 847-600-6446
 Email: international@shure.com