# VOCALS & INSTRUMENTS

## Pro-caliber sound ideal for rehearsals and gigs.

## PG48

Vocal

### Cardioid Dynamic Microphone



A professional-quality microphone optimized for spoken word and karaoke performance applications.




70Hz – 15kHz

## PG58

Vocal

### Cardioid Dynamic Microphone



A rugged, professional-quality microphone that delivers excellent sound for lead and backup vocal performance applications.




60Hz – 15kHz

## PG57

Instrument

### Cardioid Dynamic Microphone



A highly versatile, professional-quality microphone specifically designed for a wide variety of amplified and acoustic instrument applications.




50Hz – 15kHz

## PG81

Instrument

### Cardioid Condenser Microphone



Equipped with a flat frequency response that delivers clear reproduction when used in sensitive acoustic instrument applications.




40Hz – 18kHz


# Technical Specifications



## PG27
## PG27USB

Multi-Purpose




**PG27:**

| | |
|---|---|
| **Frequency Response:** | 20 Hz – 20 kHz |
| **Output Level (at 1,000 Hz):** | -41 dBV/Pa, 1 Pascal = 94 dB SPL |
| **Net Weight:** | 438 grams (15.45 ounces) |

**PG27USB:**

| | |
|---|---|
| **Frequency Response:** | 20 Hz – 20 kHz |
| **Output Level (at 1,000 Hz):** | -33 dBFS/Pa (at minimum gain) |
| **Net Weight:** | 452 grams (15.94 ounces) |


**USB Digital Recording Features:**


- Zero-Latency Monitoring
- Integrated Pre-Amp with Microphone Gain Control
- Headphone Jack
- Monitor Mix Control for blending microphone and playback audio
- 16 bit, up to 48 kHz sample rate for better-than-CD-quality audio



## PG42
## PG42USB

Vocal




**PG42:**

| | |
|---|---|
| **Frequency Response:** | 20 Hz – 20 kHz |
| **Output Level (at 1,000 Hz):** | -35 dBV/Pa, 1 Pascal = 94 dB SPL |
| **Net Weight:** | 439 grams (15.49 ounces) |

**PG42USB:**

| | |
|---|---|
| **Frequency Response:** | 20 Hz – 20 kHz |
| **Output Level (at 1,000 Hz):** | -29 dBFS/Pa (at minimum gain) |
| **Net Weight:** | 453 grams (15.98 ounces) |


**USB Digital Recording Features:**


- Zero-Latency Monitoring
- Integrated Pre-Amp with Microphone Gain Control
- Headphone Jack
- Monitor Mix Control for blending microphone and playback audio
- 16 bit, up to 48 kHz sample rate for better-than-CD-quality audio



## PG48

Vocal





| | |
|---|---|
| **Frequency Response:** | 70 Hz – 15 kHz |
| **Output Level (at 1,000 Hz):** | -52 dBV/Pa, (2.5 mV), 1 Pascal = 94 dB SPL |
| **Net Weight:** | 314 grams (11.1 ounces) |



## PG58

Vocal









| | |
|---|---|
| **Frequency Response:** | 60 Hz – 15 kHz |
| **Output Level (at 1,000 Hz):** | -53 dBV/Pa, (2.2 mV), 1 Pascal = 94 dB SPL |
| **Net Weight:** | 321 grams (11.3 ounces) |



## PG57

Instrument





| | |
|---|---|
| **Frequency Response:** | 50 Hz – 15 kHz |
| **Output Level (at 1,000 Hz):** | -56 dBV/Pa, (1.6 mV), 1 Pascal = 94 dB SPL |
| **Net Weight:** | 324 grams (11.5 ounces) |



## PG81

Instrument









| | |
|---|---|
| **Frequency Response:** | 40 Hz – 18 kHz |
| **Output Level (at 1,000 Hz):** | -48 dBV/Pa, (4.0 mV), 1 Pascal = 94 dB SPL |
| **Net Weight:** | 250 grams (8.8 ounces) less battery |



## PG52

Drum





| | |
|---|---|
| **Frequency Response:** | 30 Hz – 13 kHz |
| **Output Level (at 1,000 Hz):** | -54 dBV/Pa, (2.0 mV), 1 Pascal = 94 dB SPL |
| **Net Weight:** | 470 grams (16.8 ounces) |



## PG56

Drum




| | |
|---|---|
| **Frequency Response:** | 50 Hz – 15 kHz |
| **Output Level (at 1,000 Hz):** | -56 dBV/Pa, (1.6 mV), 1 Pascal = 94 dB SPL |
| **Net Weight:** | 323 grams (11.4 ounces) |

SHURE®
LEGENDARY PERFORMANCE™

**United States, Canada, Latin America, Caribbean:**
Shure Incorporated
5800 West Touhy Avenue
Niles, IL 60714-4608 USA

Phone: 847-600-2000
Fax: 847-600-1212 (USA)
Fax: 847-600-6446
Email: info@shure.com

**Europe, Middle East, Africa:**
Shure Europe GmbH
Jakob-Dieffenbacher-Str. 12,
75031 Eppingen, Germany

Phone: 49-7262-92490
Fax: 49-7262-9249114
Email: info@shure.de

**Asia, Pacific:**
Shure Asia Limited
22/F, 625 King's Road
North Point, Island East
Hong Kong

Phone: 852-2893-4290
Fax: 852-2893-4055
Email: info@shure.com.hk



©2012 Shure Incorporated

AL1592A 2.5K 04/12