



PGA98H

CARDIOID | CONDENSER

Instrument Microphone

Wind and brass instrument microphone with in-line preamplifier, horn clamp and choice of XLR or TA4F wireless connector.

Woodwinds · Brass



60Hz – 20kHz

PGA52

CARDIOID | DYNAMIC

Kick Drum Microphone

Ideal for low frequency performance and recording, featuring swivel joint and quick release latch for fast, flexible positioning.

Kick Drum · Bass Amp



50Hz – 12kHz

PGA56

CARDIOID | DYNAMIC

Snare/Tom Microphone

Durable, professional-quality microphone for use with close-mic snare, tom and percussion.

Snare Drum · Toms



50Hz – 15kHz

PGA98D

CARDIOID | CONDENSER

Drum Microphone

Optimized drum sound with flexible gooseneck design, molded drum mount and integrated preamplifier for phantom power.

Toms · Percussion · Snare Drum



60Hz – 20kHz

SPECIFICATIONS

Model	Type	Frequency Response	Polar Pattern	Sensitivity (at 1 kHz)	Output Impedance	Maximum SPL (at 1% kHz)	Net Weight
PGA27	Condenser	20 to 20,000 Hz	Cardioid	Open Circuit Voltage -35 dBV/Pa (17.8 mV)	115Ω	130 dB SPL Pad Off (145 dB SPL Pad On)	453 grams (16.0 oz)
PGA48	Dynamic	70 to 15,000 Hz	Cardioid	Open Circuit Voltage -53.5 dBV/Pa (2.10 mV)	600Ω	NA	300 grams (10.58 oz)
PGA52	Dynamic	50 to 12,000 Hz	Cardioid	Open Circuit Voltage -55 dBV/Pa (1.75 mV)	150Ω	NA	454 grams (16.01 oz)
PGA56	Dynamic	50 to 15,000 Hz	Cardioid	Open Circuit Voltage -57 dBV/Pa (1.45 mV)	200Ω	NA	287 grams (10.12 oz)
PGA57	Dynamic	50 to 15,000 Hz	Cardioid	Open Circuit Voltage -56.5 dBV/Pa (1.5 mV)	150Ω	NA	280 grams (9.88 oz)
PGA58	Dynamic	50 to 16,000 Hz	Cardioid	Open Circuit Voltage -55 dBV/Pa (1.79 mV)	150Ω	NA	294 grams (10.37 oz)
PGA81	Condenser	40 to 18,000 Hz	Cardioid	Open Circuit Voltage -48.5 dBV/Pa (3.8 mV)	600Ω	129.5 dB SPL	186 grams (6.56 oz)
PGA98D	Condenser	60 to 20,000 Hz	Cardioid	Open Circuit Voltage -52 dBV/Pa (2.51 mV)	850Ω	130 dB SPL	210 grams (7.41 oz)
PGA98H	Condenser	60 to 20,000 Hz	Cardioid	Open Circuit Voltage -52 dBV/Pa (2.51 mV)	850Ω	130 dB SPL	210 grams (7.41 oz)
PGA181	Condenser	50 to 20,000 Hz	Cardioid	Open Circuit Voltage -38 dBV/Pa (12.7 mV)	120Ω	138 dB SPL	383 grams (13.51 oz)

All specifications subject to change

SHURE®
LEGENDARY PERFORMANCE™

United States, Canada, Latin America, Caribbean:
Shure Incorporated
5800 West Touhy Avenue
Niles, IL 60714-4608 USA

Phone: 847-600-2000
Fax: 847-600-1212 (USA)
Fax: 847-600-6446
Email: info@shure.com

Europe, Middle East, Africa:
Shure Europe GmbH
Jakob-Dieffenbacher-Str. 12,
75031 Eppingen, Germany

Phone: 49-7262-92490
Fax: 49-7262-9249114
Email: info@shure.de

Asia, Pacific:
Shure Asia Limited
22/F, 625 King's Road
North Point, Island East
Hong Kong

Phone: 852-2893-4290
Fax: 852-2893-4055
Email: info@shure.com.hk

©2015 Shure Incorporated

AL26956 2.5K 01/15