SHURE®

SOUND ISOLATING™ EARPHONES

SE315

- Single High-Definition MicroDriver + Tuned BassPort for Full Range Audio
- Detachable Cable with Wireform Fit
- Sound Isolating™ Design
- Premium Accessories









SE315 Sound Isolating™ Earphones

Full range audio available in clear or black colour options for professional monitoring and personal listening.

Full Range Audio

Single High-Definition MicroDriver + Tuned BassPort

The SE315 features High-Definition MicroDriver + Tuned BassPort to deliver full range audio and optimised low-end performance using a vented driver.

Sound Isolating Design

Sound Isolating Technology prevents outside noise from interfering with your audio experience, whether on stage or on the go.

Unmatched Personalisation and Comfort

Ergonomic, Professional Design

- Lightweight, low-profile shape with optimised nozzle angle is designed to rest comfortably in the ear.

Detachable Cable with Wireform Fit

- Durable Kevlar® reinforced cable allows easy replacement or customisation.
- Formable wire ensures secure placement, and over the ear configuration keeps cables out of the way.
- Gold-plated MMCX Connector has a lock-snap mechanism allowing 360 degree rotation for comfortable fit.

Different Sleeve Options

- Soft, flexible sleeves gently contour to the inside of your ears.
- Multiple shapes and sizes of sleeves ensure the best possible fit and maximum isolation.

Included Accessories

3 pair Foam Sleeves (S, M, L)
3 pair Soft Flex Sleeves (S, M, L)
1 pair Yellow Foam Sleeves
1 pair Triple Flange Sleeves
Carrying Case
Cleaning Tool



SE315 Specifications

Speaker Type: Single High-Definition MicroDriver + Tuned BassPort
Sensitivity (1 kHz): 116 dB SPL/mW
Impedance (1 kHz): 27 Ω
Noise Attenuation: Up to 37 dB
Frequency Range: 22 Hz – 18.5 kHz
Input Connector: 3.5 mm, gold-plated stereo plug
Cable: 162 cm, detachable with wireform fit
Colour: Clear or black
Weight: 30 g



Stocking Details

English/German/Italian
Clear: SE315-CL-E
UPC: 042406178365
Black: SE315-K-E
UPC: 042406178426

English/French/Spanish
Clear: SE315-CL-EFS
UPC: 042406178341
Black: SE315-K-EFS
UPC: 042406178402

Package Description

Individual (Window box with flap)
Weight: 241 g
Size: 155 mm x 170 mm x 56 mm

Master Carton
Quantity: 6 units
Weight: 1.9 kg
Size: 229 mm x 178 mm x 413 mm

Europe, Middle East, Africa: Shure Europe GmbH | Wannenäckerstr. 28 | 74078 Heilbronn | Germany | www.shure.eu
UK, Ireland: Shure Distribution UK | Unit 2 The | O Centre | Lea Road | Waltham Abbey EN9 1AS | UK | www.shure.co.uk

SHURE®
LEGENDARY PERFORMANCE™

© 2010 Shure Incorporated 07/2010

Whilst every effort has been made to ensure that the information in this document is correct, we accept no liability in respect of errors or omissions.
All specifications within this document are subject to change without notice. Usage rights of the photography in this document expire in March 2012.

SE SOUND ISOLATING™ EARPHONES

EXPLODED DIAGRAM - SE315



SE315 COMPONENTS

A **Rugged Ergonomic Housing**
Ergonomic and stylish design features durable, sweat-resistant construction. Built to withstand the extremes of on-stage or everyday wear.

B **High-Definition MicroDriver + Tuned BassPort**
Housed in a uniquely designed internal assembly, the High-Definition MicroDriver delivers full range audio with a Tuned BassPort for optimised low-end performance.

C **MicroDriver Assembly**
Molded plastic design houses the MicroDriver providing protection against sudden impact. Unique built-in nozzle design with O-Ring spout configuration provides efficient audio delivery.

D **O-Ring**
A flexible ring attached to the sound outlet spout creating a seal to prevent audio leaks for accurate acoustic performance.

E **MMCX Micro-Miniature Coaxial Connector**
Gold-plated connector has a lock-snap mechanism allowing 360 degree rotation for comfortable fit.

F **Detachable with Wireform Fit Cable**
Wireform fit ensures secure placement, detachability for easy replacement or customisation, and Kevlar® reinforced for durability. Worn over the ear.

G **Nozzle**
Angled tube ensures efficient audio delivery and ergonomic fit. Directs sound to ear from internally housed built-in nozzle with O-Ring.

H **Sound Isolating Sleeves**
Selection of foam and flex sleeves create a customised fit and comfortable seal that blocks background noise.

Whilst every effort has been made to ensure that the information in this document is correct, we accept no liability in respect of errors or omissions. All specifications within this document are subject to change without notice.

Quality can not be copied • Shure against counterfeiting •

Europe, Middle East, Africa: Shure Europe GmbH | Wannenäckerstr. 28 | 74078 Heilbronn | Germany | www.shure.eu
UK, Ireland: Shure Distribution UK | Unit 2 The I O Centre | Lea Road | Waltham Abbey EN9 1AS | UK | www.shure.co.uk

© 2010 Shure Incorporated
07/2010