



SRH145/m+

NEW



Portable Headphones
Designed for immersive listening on the go

PORTABLE

FEATURES

- Rich deep bass with full range audio
- Closed-back, on-ear design for external noise isolation and comfortable fit
- Ultra-lightweight, collapsible headband for compact carrying and storage



Inline microphone and three button remote for music and calls (SRH145m+ only)

Made for iPod iPhone iPad

SRH144

NEW



Portable Semi-Open Headphones
Designed for detailed listening on the go

PORTABLE

FEATURES

- Extended range audio with enhanced high-frequency response
- Semi-open, on-ear design for natural sound and comfortable fit
- Ultra-lightweight, collapsible headband for compact carrying and storage

SRH Headphones
Specifications and Accessories

	PORTABLE		STUDIO						
									
Model	SRH144	SRH145/m+	SRH240A	SRH440		SRH550DJ	SRH750DJ	SRH840	SRH940
USE	Designed for detailed listening on the go	Designed for immersive listening on the go	Ideal for vivid listening on almost any device	Developed for professional and home studios		Designed for DJ mixing and personal listening	Engineered for live professional DJ mixing and monitoring	Optimized for professional studio recording	Designed for critical listening, monitoring and mastering
Specifications									
DESIGN	Semi-open, Supra-aural	Closed-Back, Supra-aural	Closed-Back, Circumaural	Closed-Back, Circumaural		Closed-Back, Supra-aural	Closed-Back, Circumaural	Closed-Back, Circumaural	Closed-Back, Circumaural
DRIVER	36 mm dynamic, neodymium magnet	36 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet		50 mm dynamic, neodymium magnet	50 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet
SENSITIVITY (1 kHz)	96 dB/mW	100 dB/mW	107 dB/mW	105 dB/mW		109 dB/mW	106 dB/mW	102 dB/mW	100 dB/mW
IMPEDANCE (Nominal, 1 kHz)	34 Ω	34 Ω	38 Ω	44 Ω		32 Ω	32 Ω	44 Ω	42 Ω
MAX INPUT POWER (1 kHz)	200 mW	200 mW	500 mW	500 mW		3000 mW	3000 mW	1000 mW	1000 mW
FREQUENCY RANGE	30 Hz – 20 kHz	25 Hz – 18 kHz	20 Hz – 20 kHz	10 Hz – 22 kHz		5 Hz – 22 kHz	5 Hz – 30 kHz	5 Hz – 25 kHz	5 Hz – 30 kHz
NET WEIGHT (w/o cable)	.33 lb (150 g)	.33 lb (150 g)	.52 lb (238 g)	.69 lb (311 g)		.52 lb (235 g)	.64 lb (291 g)	.82 lb (372 g)	.71 lb (322 g)
CABLE TYPE	Straight, dual-side	Straight, dual-side	Straight, attached oxygen-free copper	Coiled, single-exit, detachable oxygen-free copper		Straight, attached oxygen-free copper	Coiled, single-exit, detachable oxygen-free copper	Coiled, single-exit, detachable oxygen-free copper	Single-exit, detachable oxygen-free copper
CABLE LENGTH	1.52 m (5 ft)	1.52 m (5 ft)	2 m (6.56 ft)	3 m (9.84 ft)		2 m (6.56 ft)	3 m (9.84 ft)	3 m (9.84 ft)	Coiled: 3 m (9.84 ft) Straight: 2.5 m (8.2 ft)
PLUG	Nickel-plated 1/8" (3.5mm) stereo mini jack	Nickel-plated 1/8" (3.5mm) stereo mini jack	Gold-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack		Gold-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack
Accessories									
ADDITIONAL PAIR OF EAR PADS							OO	OO	OO
DETACHABLE CABLE									
THREADED 1/4" ADAPTER			(Nickel-Plated)						
HARD STORAGE CASE									
CARRYING BAG									