



## SRH1440

**Professional Open Back Headphones**  
Designed for mastering and critical listening

PREMIUM



### FEATURES

- Full-range audio with rich, controlled bass from 40 mm neodymium drivers
- Open-back, circumaural design for exceptionally natural sound, wide stereo image, and increased depth of field
- Ergonomically designed, fully adjustable, premium steel-frame padded headband for hours of listening comfort
- Impedance-optimized for direct connection to a wide range of portable audio devices

### INCLUDES

- Additional pair of velour ear pads
- Dual-exit, detachable cables with MMCX connectors
- Threaded 1/4" gold-plated adapter
- Zippered hard storage case

## SRH1540

**Premium Closed-Back Headphones**  
Designed for critical listening and monitoring

PREMIUM



### FEATURES

- Superior acoustic performance for an expansive soundstage with clear, extended highs and warm bass
- Closed-back, circumaural design rests comfortably over the ears and reduces background noise
- Lightweight construction featuring aircraft-grade aluminum alloy yoke and carbon fiber cap for enhanced durability
- Ergonomic dual-frame, padded headband is lightweight and fully adjustable for hours of listening comfort

### INCLUDES

- Additional pair of Alcantara™ ear pads
- Dual-exit, detachable cables with MMCX connectors
- Threaded 1/4" gold-plated adapter
- Zippered hard storage case

**SRH Headphones**  
Specifications and Accessories

PREMIUM



Model	SRH1440	SRH1540	SRH1840
<b>USE</b>	Designed for mastering and critical listening	Designed for critical listening and monitoring	Designed for mastering and critical listening
<b>Specifications</b>			
<b>DESIGN</b>	Open-Back, Circumaural	Closed-Back, Circumaural	Open-Back, Circumaural
<b>DRIVER</b>	40 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet
<b>SENSITIVITY</b> (1 kHz)	101 dB/mW	99 dB/mW	96 dB/mW
<b>IMPEDANCE</b> (Nominal, 1 kHz)	37 Ω	46 Ω	65 Ω
<b>MAX INPUT POWER</b> (1 kHz)	1000 mW	1000 mW	1000 mW
<b>FREQUENCY RANGE</b>	15 Hz – 27 kHz	5 Hz – 25 kHz	10 Hz – 30 kHz
<b>NET WEIGHT</b> (w/o cable)	.76 lb (343 g)	.63 lb (286 g)	.59 lb (268 g)
<b>CABLE TYPE</b>	Straight, dual-exit, detachable oxygen-free copper	Straight, dual-exit, detachable oxygen-free copper	Straight, dual-exit, detachable oxygen-free copper
<b>CABLE LENGTH</b>	2.1 m (6.9 ft)	1.8 m (6 ft)	2.1 m (6.9 ft)
<b>PLUG</b>	Gold-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack
<b>Accessories</b>			
<b>ADDITIONAL PAIR OF EAR PADS</b>	OO	OO	OO
<b>DETACHABLE CABLE</b>			
<b>THREADED 1/4" ADAPTER</b>			
<b>HARD STORAGE CASE</b>			
<b>CARRYING BAG</b>			



Made for iPhone 5s, iPhone 5c, iPhone 5, iPhone 4s, iPhone 4, iPhone 3GS, iPad Air, iPad mini with Retina display, iPad (4th generation), iPad mini, iPad (3rd generation), iPad 2, iPad, iPod touch (2nd through 5th generation), iPod classic, iPod nano (4th through 7th generation), and iPod shuffle (1st through 4th generation).

iPad, iPhone, iPod, iPod classic, iPod nano, iPod touch, and Retina are trademarks of Apple Inc., registered in the U.S. and other countries. iPad Air and iPad mini are trademarks of Apple Inc.