

# **SRH440**



### **Professional Studio Headphones** Developed for professional and home studios

### **FEATURES**

- Closed-back, circumaural design rests comfortably over the ears and reduces background noise
- Optimized impedance and power handling for
- Adjustable headband and collapsible construction
- Bayonet clip securely locks detachable cable into ear cup

- Enhanced frequency response delivers accurate audio across an extended range
- performance with professional audio devices
- provide comfort and portability

### **INCLUDES**

- Detachable coiled cable
- Threaded 1/4" gold-plated adapter
- Carrying bag



### PORTABLE









Model	SRH <b>144</b>	SRH <b>145/m</b> +	SRH <b>240A</b>	SRH <b>440</b>
USE	Designed for detailed listening on the go	Designed for immersive listening on the go	Ideal for vivid listening on almost any device	Developed for professional and home studios

**Specifications** 

DESIGN	Semi-open, Supra-aural	Closed-Back, Supra-aural	Closed-Back, Circumaural	Closed-Back, Circumaural
DRIVER	36 mm dynamic, neodymium magnet	36 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet	40 mm dynamic, neodymium magnet
SENSITIVITY (1 kHz)	96 dB/mW	100 dB/mW	107 dB/mW	105 dB/mW
IMPEDANCE (Nominal, 1 kHz)	34 Ω	34 Ω	38 Ω	44 Ω
MAX INPUT POWER (1 kHz)	200 mW	200 mW	500 mW	500 mW
FREQUENCY RANGE	30 Hz – 20 kHz	25 Hz – 18 kHz	20 Hz – 20 kHz	10 Hz – 22 kHz
NET WEIGHT (w/o cable)	.33 lb (150 g)	.33 lb (150 g)	.52 lb (238 g)	.69 lb (311 g)
CABLE TYPE	Straight, dual-side	Straight, dual-side	Straight, attached oxygen-free copper	Coiled, single-exit, detachable oxygen-free copper
CABLE LENGTH	1.52 m (5 ft)	1.52 m (5 ft)	2 m (6.56 ft)	3 m (9.84 ft)
PLUG	Nickel-plated 1/8" (3.5mm) stereo jack	Nickel-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack	Gold-plated 1/8" (3.5mm) stereo jack

## Accessories

ADDITIONAL PAIR OF EAR PADS			
DETACHABLE CABLE			Ø
THREADED 1/4" ADAPTER		(Nickel-Plated)	
HARD STORAGE CASE			
CARRYING BAG			